

## L<sup>A</sup>T<sub>E</sub>X examples

This document is designed to help you see how to produce some mathematical typesetting. The best way to learn how to use L<sup>A</sup>T<sub>E</sub>X is to experiment with particular commands. After you have read through this you might just try making some small changes to the .tex file and see what happens to the resulting pdf file you get.

Here is how to make the table (**2.15 Table**) near the middle of page 24 of the textbook. I chose to make the top horizontal line and the left-most vertical line as “double” lines instead of thicker lines since this latter type is a bit more difficult.

*	a	b	c
a	b	c	b
b	a	c	b
c	c	b	a

This table was typeset with the following commands.

```
\begin{center}
\begin{tabular} {c||c|c|c}
*$ & $a$ & $b$ & $c$ \\\ \hline\hline
$a$ & $b$ & $c$ & $b$ \\\ \hline
$b$ & $a$ & $c$ & $b$ \\\ \hline
$c$ & $c$ & $b$ & $a$ \\\
\end{tabular}
\end{center}
```

I wanted the table to be centered horizontally so the table is inside what is called the “center” environment. To do this I started with the `\begin{center}` command and ended with `\end{center}`. Everything between these two commands is centered. If you look closely at the table and the commands that make it, you will notice that it begins with the command

```
\begin{tabular} {c||c|c|c}
```

and ends with the command `\end{tabular}`

Everything between these commands is part of what is called the “tabular environment.” There are lots of other “environments” such as `itemize`, `center`, `enumerate`, `equation`, `align`, `eqnalign`, and many others. Each of these environments is set up to do one special thing. For example, the tabular environment is to make a table, the center environment is to center some text horizontally on a line, the enumerate environment helps you to enumerate items, and so on.

You get the idea, right?

You guessed it. That last line was typeset with

```
\begin{center}
You get the idea, right?
\end{center}
```

Now notice the rest of the command that started the tabular environment. It has a combination of vertical lines, like `|`, and four copies of the letter ‘`c`’. The fact that there are four tells L<sup>A</sup>T<sub>E</sub>X that the table will have four columns, and the vertical lines tell it where to draw vertical lines up and down the table. By the way, the letter ‘`c`’ does not stand for column but for ‘center’. The way I made the table each entry was centered in its column. You can also use ‘`r`’ for right and ‘`l`’ for left. The ‘`r`’ prints the column contents right justified; the ‘`l`’ prints the column contents left justified. Since each entry in this example was a single character, replacing ‘`c`’ by ‘`r`’ or ‘`l`’ has no visible effect. However, in the following example you can see what happens.

<i>*</i>	<i>a</i>	<i>b</i>	<i>c</i>
<i>a</i>	<i>b - a</i>	<i>c</i>	<i>b + 5c</i>
<i>b</i>	<i>a<sup>23</sup></i>	<i>c + 2d</i>	<i>b</i>
<i>c</i>	<i>c</i>	<i>b</i>	<i>a + b - c</i>

Consecutive entries in a given row of a table are separated by an `&` and each row ends with a double backslash.

Here are some typical symbols that you might use in a modern algebra class. The first of these is from Exercise 9 on page 291; the second is from near the bottom of page 421.

$\mathbb{Q}(\sqrt[3]{2}, \sqrt[3]{6}, \sqrt[3]{24})$  over  $\mathbb{Q}$   
 $\sigma_p(a+b) = (a+b)^p = a^p + b^p = \sigma_p(a) + \sigma_p(b)$ .

These two lines were typeset with the following commands

```
\noindent $\mathbb{Q}(\sqrt[3]{2}, \sqrt[3]{6}, \sqrt[3]{24})$
over $\mathbb{Q}$\
$\sigma_p(a+b)=(a+b)^p=a^p+b^p=\sigma_p(a)+\sigma_p(b)$.
```

Notice the `\noindent` at the beginning of the first line and the double backslash (`\`) at the end of the first line. It's sort of obvious what `\noindent` means. The double backslash is a command to end a line of text and begin a new line.

Here are three algebraic equations illustrating some of the common algebraic operations like fractions, powers and square roots.

$$\alpha^3 = \frac{-1+i}{\sqrt{2}}, \quad \alpha^5 = \frac{-1-i}{\sqrt{2}}, \quad \alpha^7 = \frac{1-i}{\sqrt{2}}.$$

That last line was typeset with this command.

```
\[\alpha^3=\frac{-1+i}{\sqrt{2}}, \hspace 1cm
\alpha^5=\frac{-1-i}{\sqrt{2}},
\hspace 1cm \alpha^7=\frac{1-i}{\sqrt{2}}\,. \]
```

This line is set in mathematical font and is on a line centered horizontally with a space above it and a space below the line (before the text begins again). To set off mathematics like this you start the line with the command `\[` and end it with `\]`. You can instead use `$$` to begin and `$$` to end the line. In general, putting things between a pair of dollar signs tells the program that what is between them are mathematical symbols.

There are several ways to put vertical and horizontal space in what you write. You can tell the program exactly how much space to put by putting in a command like `\vskip 2cm` which asks for a vertical skip of 2 centimeters. A horizontal skip is similar and the command would be `\hskip 2 cm`. You can ask the program to insert just a small horizontal space by using `\,`. You will find such a command in the last line of mathematics above. If you simply press the 'Enter' key twice then you get a new paragraph, but pressing it more than twice doesn't give you any more vertical space. Try it.

Sometimes it is helpful (to us and to those who read what we write) to display the simplification or expansion of an expression as an array of

equations, congruences, inequalities, etc. Here is an example of doing this to show an evaluation of a number modulo 13. (This is from **20.3 Example** on page 185 of the text. You will see that I have given this array a number so that I can easily refer to it elsewhere in my writing. Actually I didn't give it a number, but L<sup>A</sup>T<sub>E</sub>X automatically gave it a number when I decided to give it a label. Look below to the commands that generated this aligned set of congruences modulo 13. to see where I gave it a label.

$$\begin{aligned} 8^{103} &\equiv (8^{12})^8(8^7) \equiv (1^8)(8^7) \equiv 8^7 \equiv (-5)^7 \\ &\equiv (25)^3(-5) \equiv (-1)^3(-5) \equiv 5 \pmod{13}. \end{aligned} \tag{1}$$

I can now refer to this array of congruences (1).

The above was typeset using the following commands. I hope you can see that L<sup>A</sup>T<sub>E</sub>X automatically generates the numbers associated with things like arrays of equations. You can use whatever name you want as the label; L<sup>A</sup>T<sub>E</sub>X takes care of the rest. If you have other equations that you want to refer to elsewhere in the same document, then again, L<sup>A</sup>T<sub>E</sub>X handles all of the bookkeeping for you.

```
\begin{align}\label{mycongs}
8^{103} &\equiv (8^{12})^8(8^7) \equiv (1^8)(8^7) \equiv 8^7 \equiv (-5)^7\backslash
&\equiv (25)^3(-5) \equiv (-1)^3(-5) \equiv 5 \pmod{13}. \notag
\end{align}
```

```
\noindent I can now refer to this array of congruences \eqref{mycongs}.
```

Here is part of the solution to Example 11.13 on page 109

1.  $\mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$
2.  $\mathbb{Z}_2 \times \mathbb{Z}_4 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$
3.  $\mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_9 \times \mathbb{Z}_5$
4.  $\mathbb{Z}_2 \times \mathbb{Z}_4 \times \mathbb{Z}_9 \times \mathbb{Z}_5$
5.  $\mathbb{Z}_8 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$

6.  $\mathbb{Z}_8 \times \mathbb{Z}_9 \times \mathbb{Z}_5$

is typeset using

```
\begin{itemize}
\item [1.]  $\mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$ 
\item [2.]  $\mathbb{Z}_2 \times \mathbb{Z}_4 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$ 
\item [3.]  $\mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_2 \times \mathbb{Z}_9 \times \mathbb{Z}_5$ 
\item [4.]  $\mathbb{Z}_2 \times \mathbb{Z}_4 \times \mathbb{Z}_9 \times \mathbb{Z}_5$ 
\item [5.]  $\mathbb{Z}_8 \times \mathbb{Z}_3 \times \mathbb{Z}_3 \times \mathbb{Z}_5$ 
\item [6.]  $\mathbb{Z}_8 \times \mathbb{Z}_9 \times \mathbb{Z}_5$ 
\end{itemize}
```

How about some fancy “underbraces”? Here is a single line from page 249.

$$\underbrace{(1+1+\cdots+1)}_{n \text{ summands}} \underbrace{(1+1+\cdots+1)}_{m \text{ summands}} = \underbrace{(1+1+\cdots+1)}_{nm \text{ summands}}$$

typeset with

```
\[ \underbrace{(1+1+\cdots+1)}_{n \, \, \, \mbox{{\scriptsize summands}}} \underbrace{(1+1+\cdots+1)}_{m \, \, \, \mbox{{\scriptsize summands}}} = \underbrace{(1+1+\cdots+1)}_{nm \, \, \, \mbox{{\scriptsize summands}}} \]
```

In the above example the command `\,` adds a little space and the command `{\scriptsize summands}` prints the word “summands” in a font size about the same as the  $n$  or the  $m$ . The command `\mbox` allows you to insert regular text fonts inside a mathematical expression. The text you wish to put there is enclosed inside the set brackets `{` and `}`. Here the mathematical expression is put into “display mode” by the use of the delimiter `\[` at the beginning and `\]` at the end.

To get started producing your own typesetting with  $\text{\LaTeX}$  there are a couple more important things for you to know. You have to tell  $\text{\LaTeX}$  what kind of a document you are creating. You do that in the first lines of the .tex file with some commands such as

```
\documentclass[12pt]{report}
\usepackage{amsmath,amssymb,latexsym}
```

These particular commands tell the program that your document will be a report written in 12 point font. There are other document classes such as letters, articles, etc. The command `\usepackage{amsmath,amssymb,latexsym}` instructs the program to use certain packages or style files that tell it what symbols and so on to expect. There are lots of style files; it is best to consult a L<sup>A</sup>T<sub>E</sub>X manual or ask someone about these.

There are lots of other commands that allow you to set the size of the margins of your document, the width of the text, the height of text, etc. Here are several of those that I used at the top of this document. You might try experimenting with these, but you should keep in mind that some of this is quite subtle.<sup>1</sup> Consulting a L<sup>A</sup>T<sub>E</sub>X book or asking an expert is advisable.

```
\setlength{\textwidth}{7.5in}
\setlength{\leftmargin}{-.5in}
```

You also have to tell L<sup>A</sup>T<sub>E</sub>X where the actual document begins and where it ends. You have probably figured out that is done with `\begin{document}` and `end{document}` respectively. Check out the .tex file that produced this pdf file and you can see where these commands belong.

---

<sup>1</sup>See the negative left margin setting if you don't understand what I mean by subtle. By the way, please see the document "Some Helpful Examples" to see how easy it is to make footnotes in L<sup>A</sup>T<sub>E</sub>X.